


AI-3170S Touch Screen Paperless Recorder

1-32 Channels Recording and Monitoring System



Customized
User images as
flowchart
background

LINKED WITH RS485




AI-7048

22.5mm slim design with
FOUR individual SSR Output
(possible with other
YUDIAN instruments)



AI-3170S
7 inch Panel




Visualized

Up to 6 Real-Time
Line graph & bar
chart at a page



Meter	-1.4	9.0	16.3	-37.7	-25.7
Curve	14.4	22.3	23.7	53.6	-67.8
History	94	0	12	37	64
Data Rep	19.0	17.8	8.42	16.8	-8.8
Alarm Rep	1.0	-3.1	-0.53	71.2	66.9
Data Export	88	13	28	32	91
Engineer	500	6.0	18.1	Unused	Unused
Options	0.214	-11.1	21.3	0	0

Convenient:
Open box to use
Software included



Time	Object	Type	Value	Limit

Efficient:
Data exported to USB
memory
Post-processed by
analysis software included



Try Now

Download [AI-3170S Paperless Recorder Software Experience](http://www.yudian.us/attachment/download/Yudian_AI_3170_Paperless_Recorder_Experience_Version.zip) version on Windows.
http://www.yudian.us/attachment/download/Yudian_AI_3170_Paperless_Recorder_Experience_Version.zip
Email us for the password to go!

Technical Specification

Display :	7 inch , True-Color TFT LCD
Screen Resolution :	800 x 480 (VGA)
Dimension :	206W x 156H x 50D mm
Opening Dimension:	192W x 142H
Supply Voltage :	AC 220V or DC24V
Internal Memory :	90MB (approx 560 days for four channels, 1s interval)
Sampling Time :	1~60 Sec.
Protection Level :	Equivalent to IP65 (Surface)
Communication :	USB*, RS485, RS232
Operating Ambient :	Temp.-20~60 °C; humidity ≤90%RH
Printer Support :	RS232 Micro-Printer support (Printer is an accessory. It is not included.)



*** 2GB USB memory included.
Tested to support 4GB USB Thumbdrive.**

宇電(香港)自動化科技有限公司
YUDIEN (HK) AUTOMATION TECHNOLOGY CO. LIMITED
12/F, Chun Hoi Comm. Bldg., No.688 Shanghai St., Kln., H.K.
Tel: 27708785 Fax: 27708796
E-Mail : sales@yudian.com.hk
Web Site: www.yudian.com.hk